

ARTICLE CODE :

AJCAL

• **Composition :**

Wrap waterproofness: Coextruded polyethylene pipe of trilayer 80µ  
 Wrap outside: Polypropylene woven (coated inside with a polyethylene extrusion – 85 gr/m<sup>2</sup>)

**Performance :**

- MAXIMUM PRESSURE OF USE : 0.2 BAR
- PRESSURE AVERAGES OF EXPLOSION : 0.7 BAR
- CERTIFICATION AAR, PRODUCTS RECYCLABLE
- SUPPLY IN COMPRESSED AIR : MAXIMUM PRESSURE LINE 5.5 BARS

**Application Fields**

- SECURITY OF PRODUCTS AND PALLETS DURING TRANSPORT

Code	Size mm	Maxi space – mm Maritime Container	Maxi space – mm Railroad	No. pillows By Pallet	Weight by Pallet (Kg)
<b>PPW-L1 60X90</b>	600 x 900	300	-	325	120
<b>PPW-L1 90X120</b>	900X1200	400	150	275	150
<b>PPW-L1 90X150</b>	900X1500	400	150	250	160
<b>PPW-L1 90X180</b>	900X1800	400	150	250	180
<b>PPW-L1 90X210</b>	900X2100	400	150	250	200
<b>PPW-L1 90X240</b>	900X2400	400	150	250	220
<b>PPW-L1 90X270</b>	900X2700	400	150	200	230
<b>PPW-L1 120X120</b>	1200X1200	500	250	215	130
<b>PPW-L1 120X225</b>	1200X2250	500	250	175	160
<b>PPW-L1 120X240</b>	1200X2400	500	250	150	190
<b>PPW-L1 155X240</b>	1550X2400	600	400	125	210

**Size of pallets :** Width pillow 600 and 900 mm : 800 x 1200 x 1100  
 Width pillow 1200 and 1550 mm : 1600 x 1000 x 1000

AJP guarantees this product for a period of 6 months after production (see batch number)

**THE GENERAL STATEMENTS AND RECOMMANDATIONS WRITTEN IN OUR TECHNICAL SPECIFICATIONS ARE GIVEN IN GOOD FAITH. HOWEVER IT IS RECOMMENDED TO THE USER TO VERIFY THE SUITABILITY OF THE APPLICATION.**