

**ARTICLE CODE :**

**AJSTAB 140/120**

- **Composition :**  
Antislip Interlayer 140grs 2 sides

**Properties :**

- EASY TO USE
- RECYCLABLE 100 %
- REUSABLE
- NO TOXIN
- SUITED FOOD CONTACT

**Applications :**

- STABILIZE PRODUCTS
- USE MANUAL OR WITH AUTOMATIC PALETTISEURS
- EFFECTIVE FOR ALL TYPES THE GOODS

Characteristics	Unit	Standard	Value
Paper	Test to liner		
Weight	g/m <sup>2</sup>	Iso 536	<b>140</b>
Coating	2 sides		
Slip Angle	Ajstab on paper	NFQ 03-083	<b>&gt; 45°</b>
Static friction Coefficient		Iso 8295	<b>&gt; 0,9</b>
Dynamic friction Coefficient		Iso 8295	<b>&gt; 0,7</b>
Resistance	kPa	Iso 2758	<b>260</b>
Indication	kPa m <sup>2</sup> /g	Iso 2759	<b>2</b>
SCT	kN/m	Iso 9895	<b>2,30</b>

**Packaging :** Available in reels ( width 1200 mm ) and sheets. Standard size 800 x 1200 mm (5000 Sheets by pallet)  
Single or double side coating

AJP guarantees this product for a period of 6 months after production (see batch number)

**THE GENERAL STATEMENTS AND RECOMMANDATIONS WRITTEN IN OUR TECHNICAL SPECIFICATIONS ARE GIVEN IN GOOD FAITH. HOWEVER IT IS RECOMMENDED TO THE USER TO VERIFY THE SUITABILITY OF THE APPLICATION.**