

ARTICLE CODE :

AJSTAB 150/120

- **Composition :**
Antislip Interlayer 150grs 2 sides

Properties :

- EASY TO USE
- RECYCLABLE 100 %
- REUSABLE
- NO TOXIN
- SUITED FOOD CONTACT

Applications :

- STABILIZE PRODUCTS
- USE MANUAL OR WITH AUTOMATIC PALETTISEURS
- EFFECTIVE FOR ALL TYPES THE GOODS

Characteristics	Unit	Standard	Value
Paper	Test to liner		
Weight	g/m ²	Iso 536	150
Coating	2 sides		
Slip Angle	Ajstab on paper	NFQ 03-083	> 45°
Static friction Coefficient		Iso 8295	> 0,9
Dynamic friction Coefficient		Iso 8295	> 0,7
Resistance	kPa	Iso 2758	300
Indication	kPa m ² /g	Iso 2759	2
SCT	kN/m	Iso 9895	2,60

Packaging : Available in reels (width 1200 mm) and sheets. Standard size 800 x 1200 mm (5000 Sheets by pallet)
Single or double side coating

AJP guarantees this product for a period of 6 months after production (see batch number)

THE GENERAL STATEMENTS AND RECOMMANDATIONS WRITTEN IN OUR TECHNICAL SPECIFICATIONS ARE GIVEN IN GOOD FAITH. HOWEVER IT IS RECOMMENDED TO THE USER TO VERIFY THE SUITABILITY OF THE APPLICATION.