

CODE ARTICLE:

AJTAG 75/200

- Composition: HDPE neutral
- Standard width : 1000 mm
- Possibility to slit mother roll

Printing Process:

- THERMAL TRANSFER
- MATRIX PRINTING
- FLEXO PRINTING
- GRAVURE PRINTING
- SCREEN PRINTING
- OFFSET PRINTING

Application fields:

- LABELS
- MARKETING
- IML
- UNRIPABLE PROTECTION

Typical values	Test method	Unit	Values
Relative density			0.9
Thickness		microns +/- 10 %	75
Weight		gr/m ² +/- 10 %	68
Perforation resistance	DIN 53142	Nm	6
Impact resistance	DIN 53142	Nm	12
Tear resistance	DIN 53363	N/mm thickness	58
Ultimate tensile load	DIN 53455	kN/m	3.7
Ultimate tensile stress	DIN 53455	MPa	49
Elongation	DIN 53455	%	190
Temperature range		° C	- 40 à + 90 °C

AJP guarantees this product for a period of 6 months after production (see batch number)

Sheets available on request

Pantone colours available from 4000 m²

THE GENERAL STATEMENTS AND RECOMMANDATIONS WRITTEN IN OUR TECHNICAL SPECIFICATIONS ARE THE RESULTS OF TESTS IN OUR LABORATORY AND ARE GIVEN IN GOOD FAITH. HOWEVER IT IS RECOMMENDED TO THE USER TO VERIFY THE SUITABILITY OF THE APPLICATION, INKS, MATERIAL AND EQUIPMENT.