

**CODE ARTICLE:**

**AJTAG 100/213**

- Composition: HDPE Coated 1 side
- Standard width : 1000 mm
- Possibility to slit mother roll

**Printing Process:**

- THERMAL TRANSFER
- MATRIX PRINTING
- FLEXO PRINTING
- GRAVURE PRINTING
- SCREEN PRINTING
- OFFSET PRINTING

**Application fields:**

- LABELS
- MARKETING
- IML
- UNRIPABLE PROTECTION

Typical values	Test method	Unit	Values
Relative density			<b>0.9</b>
Thickness		microns +/- 10 %	<b>105</b>
Weight		gr/m <sup>2</sup> +/- 10 %	<b>95</b>
Perforation resistance	DIN 53142	Nm	<b>6</b>
Impact resistance	DIN 53142	Nm	<b>8</b>
Tear resistance	DIN 53363	N/mm thickness	<b>80</b>
Ultimate tensile load	DIN 53455	kN/m	<b>4.5</b>
Ultimate tensile stress	DIN 53455	MPa	<b>45</b>
Elongation	DIN 53455	%	<b>170</b>
Temperature range		° C	<b>- 40 to + 90 °C</b>

AJP guarantees this product for a period of 6 months after production (see batch number)  
 Sheets available on request  
 Pantone colours available from 4000 m<sup>2</sup>

**THE GENERAL STATEMENTS AND RECOMMANDATIONS WRITTEN IN OUR TECHNICAL SPECIFICATIONS ARE THE RESULTS OF TESTS IN OUR LABORATORY AND ARE GIVEN IN GOOD FAITH. HOWEVER IT IS RECOMMENDED TO THE USER TO VERIFY THE SUITABILITY OF THE APPLICATION, INKS, MATERIAL AND EQUIPMENT.**